



**FCC 47 CFR PART 15 SUBPART B**

**TEST REPORT**

**FOR**

**HD-SDI TO HDMI CONVERTER**

Model: SDI0XXX

Trade Name: Acrosser

Issued to

Smart Cabling & Transmission Corp.  
10F, No. 493, Chung-Cheng Rd., Hsin Tien Dist., New Taipei City 231, Taiwan, R.O.C.

Issued by

PEP Testing Laboratory

<b>EMC Test Site</b>	<b>Xizhi office and Lab</b>	<b>12F.-3, No.27-1, Ln. 169, Kangning St., Xizhi Dist., New Taipei City 221, Taiwan (R.O.C.)</b>
--------------------------	---------------------------------	--

*Note: This test refers exclusively to the test presented test model and sample. This report shall not be reproduced except in full, without the written approval of PEP Testing Laboratory. This document may be altered or revised by PEP Testing Laboratory. Personnel only, and shall be noted in the revision section of the document.*



<b>TABLE OF CONTENTS</b> -----	<b>2</b>
<b>1. GENERAL INFORMATION</b> -----	<b>3</b>
1.1 DESCRIPTION OF THE TESTED SAMPLES-----	4
1.2 I/O PORT OF THE EUT-----	4
1.3 TEST METHODOLOGY-----	5
1.4 DESCRIPTION OF THE SUPPORT EQUIPMENTS-----	6
1.5 FEATURES OF EUT: PLEASE REFER TO USER MANUAL OR PRODUCT SPECIFICATION.-----	6
<b>2. INSTRUMENT AND CALIBRATION</b> -----	<b>7</b>
2.1 MEASURING INSTRUMENT CALIBRATION-----	7
2.2 TEST AND MEASUREMENT EQUIPMENT-----	7
2.3 TEST PERFORMED-----	8
2.4 APPENDIX-----	9
<b>3. CONDUCTED EMISSION MEASUREMENT</b> -----	<b>12</b>
3.1 TEST SET-UP (PLEASE REFER TO APPENDIX 1)-----	12
3.2 LIMIT-----	12
3.3 TEST PROCEDURE-----	12
3.4 TEST SPECIFICATION-----	13
3.5 RESULT: PASSED-----	13
3.6 TEST DATA:-----	13
<b>4. RADIATED EMISSION MEASUREMENT</b> -----	<b>14</b>
4.1 TEST SETUP (PLEASE REFER TO APPENDIX 1)-----	14
4.2 LIMIT-----	15
4.3 TEST PROCEDURE-----	15
4.4 TEST SPECIFICATION-----	15
4.5 RESULT: PASSED-----	15
4.6 TEST DATA:-----	16
<b>5. MEASUREMENT UNCERTAINTY</b> -----	<b>17</b>
<b>APPENDIX 1</b>	
<b>PHOTOS OF TEST CONFIGURATION</b>	
<b>APPENDIX 2</b>	
<b>TEST DATA</b>	
<b>PHOTOS OF EUT</b>	



**1. GENERAL INFORMATION**

**Applicant** : Smart Cabling & Transmission Corp.  
**Address** : 10F, No. 493, Chung-Cheng Rd., Hsin Tien Dist., New Taipei City 231, Taiwan, R.O.C.  
**Manufacturer** : Smart Cabling & Transmission Corp.  
**Address** : 10F, No. 493, Chung-Cheng Rd., Hsin Tien Dist., New Taipei City 231, Taiwan, R.O.C.  
**EUT** : HD-SDI TO HDMI CONVERTER  
**Model Name** : SDI0XXX  
**Model Differences** : N/A

Is herewith confirmed to comply with the requirements set out in the FCC Rules and Regulations Part 15 Subpart B and CISPR PUB. 22 and the measurement procedures were according to ANSI C63.4-2003. The said equipment in the configuration described in this report shows the maximum emission levels emanating from equipment are within the compliance requirements.

**FCC part 15 subpart B**

**ICES-003**

**Class B**

Receipt Date : 06/07/2012

Final Test Date : 06/22/2012

**Tested By:**

**Reviewed by:**

JUN. 22, 2012  
**Date**

*S.k chang*

S.K. Chang/ Engineer

JUN. 22, 2012  
**Date**

*Alex Chou*

Alex Chou / Manager

Designation Number: TW1046



**1.1 DESCRIPTION OF THE TESTED SAMPLES**

EUT Type :  Engineer Type

Condition when received :  Good

EUT Name : HD-SDI TO HDMI CONVERTER

Model Number : SDIOXXX

Receipt Date : 06/07/2012

EUT Power Rating :  AC Power  
 DC Power  
 DCV from PC  
 DCV from Adaptor

AC Power Adaptor Rating : Input 100-240Vac, 50/60Hz, 0.2A  
Output 5Vdc, 1A

AC Power Cord Type : 0.8 m  Un-Shielded  Shielded

**1.2 I/O PORT OF the EUT**

I/O port type	Q'ty	Tested with
BNC Port	2	2
HDMI Port	1	1



### **1.3 TEST METHODOLOGY**

#### **EUT SYSTEM OPERATION**

1. The EUT was configured according to ANSI C63.4 Section 5.2, 7.1, 7.2 & CISPR 22.
2. Photos of test configuration please refer to appendix 1.
3. Perform the EMC testing procedures, and measure the maximum emission noise.



### 1.4 DESCRIPTION OF THE SUPPORT EQUIPMENTS

#### Setup Diagram

See test photographs attached in appendix I for the actual connections between EUT and support equipment.

#### Support Equipment

Peripherals Devices:

OUTSIDE SUPPORT EQUIPMENT							
No.	Equipment	Model	Serial No.	FCC ID/ BSMI ID	Trade name	Data Cable	Power Cord
1.	MONITOR	PD-70FA	49430248K P01429	4892A060	compaq	Shielded 1.6m	Unshielded 1.8m
2.	MONITOR	2212Ph	E9777JA00 166	R33037	AOC	Shielded 1.8m	Unshielded 1.8m
3.	CCD	N/A	N/A	N/A	SHANY	N/A	N/A
EUT							
No.	Equipment	Model	Serial No.	FCC ID/ BSMI ID	Trade name	Data Cable	Power Cord
1.	Main Board	N/A	N/A	N/A	N/A	N/A	N/A
2.	Adaptor	DSC-6PFA-0 5 FEU 050100	N/A	N/A	DVE	N/A	Unshielded 0.8m

**Note:** All the above equipment /cable were placed in worse case position to maximize emission signals during emission test.

**Grounding:** Grounding was in accordance with the manufacturer's requirement and conditions for the intended use.

### 1.5 FEATURES OF EUT: PLEASE REFER TO USER MANUAL OR PRODUCT SPECIFICATION.



## 2. INSTRUMENT AND CALIBRATION

### 2.1 MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in the report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

### 2.2 TEST AND MEASUREMENT EQUIPMENT

The following list contains measurement equipment used for testing. The equipment conforms to the requirement of CISPR 16-1, ANSI C63.2 and. Other required standards.

Calibration of all test and measurement, including any accessories that may effect such calibration, is checked frequently to ensure the accuracy. Adjustments are made and correction factors are applied in accordance with the instructions contained in the respective.

**TABLE LIST OF TEST AND MEASUREMENT EQUIPMENT**

Conducted Emission Measurement					
Instrument	Manufacturer	Model No.	Serial No.	Calibration Due Date	Note
RF Cable	MIYAZAKI&ANRITSU	RG 58A&MP59B	M79094	Apr.08,2013	
LISN	Rolf Heine Hochfrequenztechnik	NNB-2/16z	98062	Jan.16,2013	
Spectrum Analyzer	ADVANTEST	R3261C	87120343	Mar.28,2013	
EMI Test Receiver	R&S	EAHS-10	1093.4495.03	Mar.21,2013	
Radiated Emission Measurement					
Instrument	Manufacturer	Model No.	Serial No.	Calibration Due Date	Note
EMC Test Receiver	LIG NEx1	ER-265	L0907B006	7-Nov-12	
Bilog Antenna	SUNOL	JB1	A052204	27-Jun-12	
Turn table	EMCO	2080	9508-1805	N/A	
Controller	EMCO	2090	9804-1328	N/A	
Preamplifier	WIRELESS	FPA6592G	60017	11-Aug-12	
RF Cable	JYE BAO	RG214/U	25M-002	1-Nov-12	
Thermo-Hygro meter	WISEWIND	4-INU-1	50100378	2-Nov-12	



---

Double Ridged Guide HORN ANTENNA	SCHWADZBECK	BBHA9120D	491	31-Oct-12	
Microwave Preamplifier	SCHWADZBECK	BBV 9718	9718-008	7-Nov-12	
Microflex Cable	HUBER SUHNER	SUCOFLEX 104	302339/4	7-Nov-12	
Microflex Cable	HUBER SUHNER	SUCOFLEX 104	N/A	7-Nov-12	

✧ Calibration interval of instruments listed above is one year

### **2.3 TEST PERFORMED**

Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver which bandwidth is set at 9KHz.

Radiated emissions were investigated over the frequency range from 30MHz to 1000MHz using a receiver which bandwidth is set at 120KHz. Radiated measurement was performed at distance that from an antenna to EUT is 10meters.



## 2.4 APPENDIX

### **Appendix A: Measurement Procedure for Main Power Port Conducted Emissions**

The measurements are performed in a Global lab's room; The EUT was placed on non-conductive 1.0m x 1.5m table, which is 0.8 meters above an earth-grounded.

Power to the EUT was provided through the LISN which has the Impedance (50ohm/50uH) vs. Frequency Characteristic in accordance with the standard. Powers to the LISNs were filtered to eliminate ambient signal interference and these filters were bonded to the ground plane. Peripheral equipment required to provide a functional system (support equipment) for EUT testing was powered from the second LISN through a ganged, metal power outlet box which is bonded to the ground plane at the LISN.

If the EUT is supplied with a flexible power cord, the power cord length in excess of the distance separating the EUT from the LISN shall be folded back and forth at the center of the lead so as to form a bundle not exceeding 40cm in length. If the EUT is provided with a permanently coiled power cord, bundling of the cord is not required. If the EUT is supplied without a power cord, the EUT shall be connected to the LISN by a power cord of the type specified by the manufacturer which shall not be longer than 1 meter. The excess power cord shall be bundled as described above. If a non-flexible power cord is provided with the EUT, it shall be cut to the length necessary to attach the EUT to the LISN and shall not be bundled.

The interconnecting cables were arranged and moved to get the maximum measurement. Both the line of power cord, hot and neutral, were measured.

The highest emissions were analyzed in details by operating the spectrum analyzer in fixed tuned mode to determine the nature of the emissions and to provide information which could be useful in reducing their amplitude.

### **Appendix B: Test Procedure for Radiated Emissions**

#### **Preliminary Measurements in the Anechoic Chamber**

The radiated emissions are initially measured in the anechoic chamber at a measurement distance of 3 meters. Desktop EUT are placed on a wooden stand 0.8 meter in height. The measurement antenna is 3 meters from the EUT. The test setup in anechoic chamber is the same as open site. The turntable rotated 360°. The antenna height is 1m. The primary objective of the radiated measurements in the anechoic chamber is to identify the frequency spectrum in the absence of the electromagnetic environment existing on the open test site. The frequencies can then be pre-selected on the open test site to obtain the corresponding amplitude. The initial scan is made with the spectrum analyzer in automatic sweep mode. The spectrum peaks are then measured manually to determine the exact frequencies.

#### **Measurements on the Open Site or Chamber**

The radiated emissions test will then be repeated on the open site or chamber to measure the amplitudes accurately and without the multiple reflections existing in the shielded room. The EUT and support equipments are set up on the turntable. Desktop EUT are set up on a wooden stand 0.8 meter above the ground.

For the initial measurements, the receiving antenna is varied from 1-4 meter height and is changed in the vertical plane from vertical to horizontal polarization at each frequency. Both



reading are recorded with the quasi-peak detector with 120KHz bandwidth. For frequency between 30 MHz and 1000MHz, the reading is recorded with peak detector or quasi-peak detector.

At the highest amplitudes observed, the EUT is rotated in the horizontal plane while changing the antenna polarization in the vertical plane to maximize the reading. The interconnecting cables were arranged and moved to get the maximum measurement. Once the maximum reading is obtained, the antenna elevation and polarization will be varied between specified limits to maximize the readings.



## **Appendix C: Warning Labels**

### **Label Requirements**

A Class B digital device subject to certification by the FCC shall carry a warning label which includes the following statement:

**\*\*\* WARNING \*\*\***

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

## **Appendix D: Warning Statement**

### **Statement Requirements**

The operator's manual for a Class A digital device shall contain the following statements or their equivalent:

**\*\*\* WARNING \*\*\***

This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at his own expense.

Notice: The changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.


\* \* \* \* \*

If the EUT was tested with special shielded cables the operator's manual for such product shall also contain the following statements or their equivalent:

Shielded interface cables and/or AC power cord, if any, must be used in order to comply with the emission limits.

### 3. CONDUCTED EMISSION MEASUREMENT

#### 3.1 TEST SET-UP (PLEASE REFER TO APPENDIX 1)



#### 3.2 LIMIT

Frequency range (MHz)	CLASS A		CLASS B	
	QP dB(uV)	Average dB(uV)	QP dB(uV)	Average dB(uV)
0.15-0.5	79 dBuV	66 dBuV	66 - 56 dBuV	56 - 46 dBuV
0.5-5.0	73 dBuV	60 dBuV	56 dBuV	46 dBuV
5.0-30.0	73 dBuV	60 dBuV	60 dBuV	50 dBuV

Remark: In the above table, the tighter limit applies at the band edges.

#### 3.3 TEST PROCEDURE

The EUT and simulators are connected to the main power through a line impedance stabilization network (LISN). It provides a 50 ohm / 50 μH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50 ohm / 50 μH coupling impedance with 50 ohm termination. (Please refer to the block diagram of the test setup and photograph.)

Both sides of AC line are checked for the maximum conducted emission interference. In order to find the maximum emissions, the relating positions of equipment and all of the interference cables must be changed according to CISPR22 regulation: The measurement procedure on conducted emission interference.

The resolution bandwidth of the field strength meter is set at 9KHz



**3.4 TEST SPECIFICATION**

ANSI C63.4 – 2003 Section 5.2, 7.1, 7.2 & CISPR 22 CLASS B

**3.5 RESULT: PASSED**

EMI Receiver/Spectrum Analyzer Configuration (for the frequencies tested)


Frequency Range:	150KHz--30MHz
Detector Function:	Quasi-Peak / Average Mode
Resolution Bandwidth:	9KHz

**3.6 TEST DATA:**

**Please refer to appendix 2.**

#### 4. RADIATED EMISSION MEASUREMENT

##### 4.1 TEST SETUP (PLEASE REFER TO APPENDIX 1)





**4.2 LIMIT**

Frequency MHz	Class A		Class B	
	Distance (Meter)	Limit dB $\mu$ V/m	Distance (Meter)	Limit dB $\mu$ V/m
30 ~ 230	10	40	10	30
230 ~ 1000	10	47	10	37

Frequency range GHz	Average limit dB( $\mu$ V/m)	Peak limit dB( $\mu$ V/m)
Above 1000	54	74

Remark: In the above table, the tighter limit applies at the band edges

**4.3 TEST PROCEDURE**

The EUT and its simulators are placed on turn table, non-conductive and wooden table, which is 0.8 meter above ground. The turn table rotates 360 degrees to determine the position of the maximum emission level. For the frequency range is below 1 GHz, the EUT was positioned such that distance from antenna to the EUT is 10 meters. For the frequency range is above 1 GHz, the EUT was positioned such that distance from antenna to the EUT is 3 meters.

For the frequency range is below 1 GHz, the antenna is moved up and down between 1 meter and 4 meters to receive the maximum emission level.

Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission, all of the interference cables must be manipulated according to EN 55022 regulation: the test procedure of the radiated emission measurement.

The bandwidth set on the field strength is 120 KHz when the frequency range is below 1GHz. The bandwidth set on the field strength is 1 MHz when the frequency range is above 1GHz.

**4.4 TEST SPECIFICATION**

ANSI C63.4 – 2003 Section 5.2, 7.1, 7.2 & CISPR 22 CLASS B

**4.5 RESULT: PASSED**

The radiated mission test was passed at minimum margin :  
Vertical 196.84 MHz/ 24.77 dBuV/m, Antenna Height 2.72 Meter,  
Turn Table 181 degree.



**4.6 TEST DATA:**

**Please refer to appendix 2.**



## 5. MEASUREMENT UNCERTAINTY

The uncertainty is calculated in accordance with CISPR16-4-2, the total uncertainty for this test is as follows:

### Uncertainty of Conducted Emission Measurement

Contribution	Probability Distribution	150KHz – 30MHz
Receiver reading	Normal (k=2)	±0.2
Cable loss	Normal (k=2)	±0.1
AMN insertion loss	Rectangular	±0.2
RCV/SPA specification	Rectangular	±0.9
combined standard uncertainty $U_e(y)$	normal	±1.0
Measuring uncertainty for a level of confidence of 95% $U=2U_e(y)$	normal (k=2)	±2.0

### Uncertainty of Radiated Emission Measurement

Contribution	Probability Distribution	30MHz~1GHz
Receiver reading	Normal (k=2)	±0.2
Cable loss calibration	Normal (k=2)	±0.1
Antenna factor calibration	Rectangular	±0.4
Pre Amplifier Gain calibration	Rectangular	±0.3
RCV/SPA specification	Rectangular	±0.9
combined standard uncertainty $U_e(y)$	normal	±1.1
Measuring uncertainty for a level of confidence of 95% $U=2U_e(y)$	normal (k=2)	±2.2



**SAMPLE OF FCC VERIFICATION LABEL 1**

This device complies with part 15 of the FCC Rules.  
Operation is subject to the following two conditions: (1)  
This device may not cause harmful interference. And (2)  
this device must accept any interference received, including  
interference that may cause undesired operation.

**SAMPLE OF FCC DoC LABEL 2**



Trade Name  
Model Number

## **Appendix 1**

### **PHOTOS OF TEST CONFIGURATION**

01 CON-F



02 CON-R




**Appendix 2**  
**TEST DATA**



Data: 3

File: D:\CON數據\案件數據\12060704\12060704-101-0615.EM6 (4)

Date: 2012-06-15 Time: 17:03:12



Site : CLAMP

Condition: CISPR22 CLASS-B QP CON-LISN(101-0413) NEUTRAL

EUT : Please refer to page 1 of report

MODEL : Please refer to page 1 of report

MEMO :

T/H :


	Freq	Read Level	Level	Factor	Over Limit	Limit Line	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	
1	0.16	49.83	49.73	-0.10	-15.70	65.43	Peak
2	0.38	43.93	43.80	-0.13	-14.41	58.21	Peak
3	0.78	33.33	33.17	-0.16	-22.83	56.00	Peak
4	2.95	28.47	28.19	-0.28	-27.81	56.00	Peak
5	6.56	38.90	38.53	-0.37	-21.47	60.00	Peak
6	27.13	40.12	39.34	-0.78	-20.66	60.00	Peak



Data: 4

File: D:\CON數據\案件數據\12060704\12060704-101-0615.EM6 (4)

Date: 2012-06-15 Time: 17:03:48



Site : CLAMP

Condition: CISPR22 CLASS-B QP CON-LISN(101-0413) LINE

EUT : Please refer to page 1 of report

MODEL : Please refer to page 1 of report

MEMO :

T/H :


	Freq	Read Level	Level	Factor	Over Limit	Limit Line	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	
1	0.16	50.27	50.17	-0.10	-15.26	65.43	Peak
2	0.38	43.39	43.26	-0.13	-15.04	58.30	Peak
3	0.84	33.14	32.98	-0.16	-23.02	56.00	Peak
4	2.81	29.06	28.80	-0.26	-27.20	56.00	Peak
5	6.70	35.85	35.48	-0.37	-24.52	60.00	Peak
6	27.13	30.40	29.66	-0.74	-30.34	60.00	Peak



Data: 3

File: C:\Documents and Settings\CH\桌面案件\12060704\12060704-DATA\12060704-101-0615.EM6 (

Date: 2012-06-19 Time: 09:29:33




Site : open site  
 Condition: CISPR22 CLASS B 10m 9161(30M-1G)-101-H HORIZONTAL  
 EUT : Please refer to page 1 of report  
 MODEL : Please refer to page 1 of report  
 MEMO :

	Freq	Level	Read	Over	Limit	Remark
	MHz	dBuV/m	Level	Factor	Limit	
			dBuV	dB/m	dB	dBuV/m
1	198.78	18.83	38.55	-19.72	-11.17	30.00 QP
2	225.94	20.28	36.41	-16.13	-9.72	30.00 QP
3	378.23	21.27	31.57	-10.30	-15.73	37.00 QP
4	470.38	25.29	34.48	-9.19	-11.71	37.00 QP
5	567.38	26.81	33.31	-6.50	-10.19	37.00 QP
6	745.86	28.39	31.89	-3.50	-8.61	37.00 QP



Data: 4 File: C:\Documents and Settings\CH\桌面案件\12060704\12060704-DATA\12060704-101-0615.EM6 (



Site : open site  
Condition: CISPR22 CLASS B 10m 9161(30M-1G)-101-V VERTICAL  
EUT : Please refer to page 1 of report  
MODEL : Please refer to page 1 of report  
MEMO :

	Freq	Level	Read	Over	Limit	Remark
	MHz	dBuV/m	Level	Factor	Limit	Line
			dBuV	dB/m	dB	dBuV/m
1	138.64	23.23	38.56	-15.33	-6.77	30.00 QP
2 !	196.84	24.77	41.88	-17.11	-5.23	30.00 QP
3	258.92	23.66	40.83	-17.17	-13.34	37.00 QP
4 !	268.62	33.37	49.41	-16.04	-3.63	37.00 QP
5	319.06	23.79	38.61	-14.82	-13.21	37.00 QP
6	565.44	24.45	33.44	-8.99	-12.55	37.00 QP