



Certificate of Conformity

The products

EUT : **VGA & Stereo Audio/Digital CAT5
Extender and Distributor**
Model No. : **VEXXDALX**

which produced by

SMART CABLING & TRANSMISSION CORP.
10F, No.493, Chung-Cheng Rd., Hsin Tien City, Taipei County, 231, Taiwan

Has been tested by Electronics Testing Center, Taiwan ETC
And was found to comply with the EMC requirements of Directive 2004/108/EC on the basis of

EN 55022:2006/A1:2007(Class B)
EN 61000-3-2:2006/A1:2009/A2:2009
EN 61000-3-3:2008

EN 55024:1998/A1:2001/A2:2003

Signature
Will Yauo

Manager of EMC Testing Department II
Electronics Testing Center, Taiwan



Report Number : 11-02-RBF-094

Date of Issue: Jul. 07, 2011

- Note:
1. The results of the Test Report relate only to the items tested.
 2. The Test Report shall not be reproduced except in full, without the written approval of ETC.
 3. Together with the applicant's own documented production control, the applicant (or his European authorized representative) could draw up an EC Declaration of Conformity and affix the CE marking.
 4. EC Declaration of Conformity is the responsibility of the manufacturer/ importer.

ELECTRONICS TESTING CENTER, TAIWAN
No.34, Lin 5, Dingfu Vil., Linkou Dist., New Taipei
City, Taiwan 24442, R.O.C.

TEL:(02)26023052
INT:+886-2-26023052
FAX:(02)26010910
INT:+886-2-26010910



EMC

TEST REPORT

Responsible Party : ***SMART CABLING & TRANSMISSION CORP.***

Manufacturer : ***SMART CABLING & TRANSMISSION CORP.***

Description of Product : ***VGA & Stereo Audio/Digital CAT5 Extender and Distributor***

Model No. : ***VEXXDALX***

Test Report File No. : ***11-02-RBF-094***

Date Test Item Received : ***Feb. 19, 2011***

Date Test Campaign Completed : ***Jun. 21, 2011***

Date of Issue : ***Jul. 07, 2011***

Test Performed by

ELECTRONICS TESTING CENTER (ETC) , TAIWAN

No.34, Lin 5, Dingfu Vil., Linkou Dist.,

New Taipei City, Taiwan 24442, R.O.C.

TEL : (02)26023052 FAX : (02)26010910

[http:// www.etc.org.tw](http://www.etc.org.tw) ; e-mail: emc@etc.org.tw

This test report consists of 52 Pages. This test report is the property of ETC, and shall not be reproduced except in full, without the written consent of ETC. ETC hereby returns all rights-in-data to [***SMART CABLING & TRANSMISSION CORP.***] for their exclusive legal use.

Note : 1. The results of the Test Report relate only to the items tested.
2. The Test Report shall not be reproduced except in full , without the written approval of ETC.

CONTENTS

●	EMC TEST REPORT.....	1
●	CONTENTS.....	2
1	TEST REPORT CERTIFICATION.....	5
2	GENERAL INFORMATIONS	7
2.1	Description of EUT.....	7
2.2	Related Information of EUT	7
2.3	Tested Configuration.....	7
2.4	Deviation Record	8
2.5	Measurement Uncertainty	8
2.6	Description of Test Mode.....	8
2.7	Modification Record	8
3	SUMMARY OF TEST RESULTS	9
3.1	Emissions	9
3.1.1	Conducted Emissions	9
3.1.2	Conducted Telecommunication ports.....	9
3.1.3	Radiated Emissions	9
3.1.4	Harmonics Current Emissions.....	10
3.1.5	Voltage Fluctuations and Flicker.....	10
3.2	Immunity.....	11
3.2.1	Immunity Criteria.....	11
3.2.2	Electrostatic Discharge Immunity.....	11
3.2.3	RF Radiated Fields Immunity	11
3.2.4	EFT/Burst Immunity	12
3.2.5	Surge Immunity.....	12
3.2.6	RF Common Mode Immunity.....	12
3.2.7	Power Frequency Magnetic Field Immunity.....	12
3.2.8	Voltage Interruptions and Voltage Dips Immunity.....	12
4	TEST DATA & RELATED INFORMATIONS.....	13
4.1	Emissions	13
4.1.1	Conducted Emissions Test	13
4.1.1.1	Limit of Conducted Emission Measurement.....	13
4.1.1.2	Test Instruments	13
4.1.1.3	Conducted Emissions Test Data.....	14
4.1.1.4	Conducted Emissions Test Setup Photos	17
4.1.2	Conducted Telecommunication ports Test	18

4.1.2.1	Conducted Telecommunication ports Test Data.....	18
4.1.3	Radiated Emissions Test.....	19
4.1.3.1	Limit of Radiated Emission Measurement.....	19
4.1.3.2	Test Instruments	19
4.1.3.3	Radiated Emissions Test Data	20
4.1.3.4	Radiated Emissions Test Setup Photos.....	24
4.1.4	Harmonics Current Emissions Test	25
4.1.4.1	Test Instruments	25
4.1.4.2	Harmonics Current Emissions Test Data	25
4.1.4.3	Harmonics Current Emissions Test Setup Photos	27
4.1.5	Voltage Fluctuations and Flicker Test	28
4.1.5.1	Test Instruments	28
4.1.5.2	Voltage Fluctuations and Flicker Test Data.....	28
4.1.5.2	Voltage Fluctuations and Flicker Test Setup Photos	29
4.2	Immunity	30
4.2.1	Electrostatic Discharge Immunity Test	30
4.2.1.1	Test Instruments	30
4.2.1.2	Electrostatic Discharge Immunity Test Data.....	30
4.2.1.3	Electrostatic Discharge Immunity Test Setup Photos	34
4.2.2	RF Radiated Fields Immunity Test.....	35
4.2.2.1	Test Instruments	35
4.2.2.2	RF Radiated Fields Immunity Test Data.....	35
4.2.2.3	RF Radiated Fields Immunity Test Setup Photos.....	37
4.2.3	EFT/Burst Immunity Test.....	38
4.2.3.1	Test Instruments	38
4.2.3.2	EFT/Burst Immunity Test Data.....	38
4.2.3.3	EFT/Burst Immunity Test Setup Photos.....	40
4.2.4	Surge Immunity Test	41
4.2.4.1	Test Instruments	41
4.2.4.2	Surge Immunity Test Data.....	41
4.2.4.3	Surge Immunity Test Setup Photos	43
4.2.5	RF Common Mode Immunity Test	44
4.2.5.1	Test Instruments	44
4.2.5.2	RF Common Mode Immunity Test Data.....	44
4.2.5.3	RF Common Mode Immunity Test Setup Photos	46
4.2.6	Power Frequency Magnetic Field Immunity Test.....	47
4.2.6.1	Test Instruments	47
4.2.6.2	Power Frequency Magnetic Field Immunity Test Data	47
4.2.6.3	Power Frequency Magnetic Field Immunity Test Setup Photos	49

- 4.2.7 Voltage Interruptions and Voltage Dips Immunity Test 50
 - 4.2.7.1 Test Instruments 50
 - 4.2.7.2 Voltage Interruptions and Voltage Dips Immunity Test Data..... 50
 - 4.2.7.3 Voltage Interruptions and Voltage Dips Immunity Test Setup Photos 52

1 TEST REPORT CERTIFICATION

Client : SMART CABLING & TRANSMISSION CORP.
Address : 10F, No.493, Chung-Cheng Rd., Hsin Tien City, Taipei County, 231, Taiwan
Manufacturer : SMART CABLING & TRANSMISSION CORP.
Address : 10F, No.493, Chung-Cheng Rd., Hsin Tien City, Taipei County, 231, Taiwan

EUT : VGA & Stereo Audio/Digital CAT5 Extender and Distributor
Model No. : VEXXDALX
Test specifications :
Emissions : EN 55022:2006/A1:2007 (Class B)
EN 61000-3-2:2006/A1:2009/A2:2009
EN 61000-3-3:2008

Immunity : IEC61000-4-2:2008
IEC61000-4-3:2006/A1:2007/A2:2010
IEC61000-4-4:2004/A1:2010
IEC61000-4-5:2005
IEC61000-4-6:2008
IEC61000-4-8:2009
IEC61000-4-11:2004

Regulations applied :
Emissions : EN 55022:2006/A1:2007 (Class B)
EN 61000-3-2:2006/A1:2009/A2:2009
EN 61000-3-3:2008

Immunity : EN 55024:1998/A1:2001/A2:2003

The testing described in this report has been carried out to the best of our knowledge and ability, and our responsibility is limited to the exercise of reasonable care. This certification is not intended to relieve the sellers from their legal and/or contractual obligations. Besides, the "Comment Issues" highlight above is important information for this test report. Responsible must read carefully about the description.

Test Engineer : Tien-Lu Liao
(Tien-Lu Liao, Engineer)

Check By : Charles Wang
(Charles Wang, Supervisor)

Approve & Authorized : Will Yao
Will Yao, Manager
EMC Dept. II of ELECTRONICS
TESTING CENTER, TAIWAN



Laboratory Introduction: Electronics Testing Center, Taiwan is recognized, filed and mutual recognition arrangement as following:

- ① ISO9002 : BSMI, TÜV Product Service
- ② ISO/IEC 17025 : BSMI, CNLA, DGT, NVLAP, CCIBLAC, UL, Compliance
- ③ EN45001 : TÜV Rheinland, NEMKO, FIMKO, SGS
- ④ Filing : FCC, Industry Canada, VCCI
- ⑤ MRA : Australia, Hong Kong, New Zealand, Singapore, USA, Japan, Korea, China, APLAC through CNLA

2 GENERAL INFORMATIONS

2.1 Description of EUT

VGA&Stereo Audio/Digital Cat5 Extender and Distributor

2.2 Related Information of EUT

Size of EUT : 126mm x 96mm x 31mm

Power Supply : I/P:100-240Vac,50/60Hz,0.5A
O/P:DC5V,2A

Highest working

Frequency : 4MHz

* For more detailed features, please refer to *User's Manual*.

2.3 Tested Configuration

The EUT connected with other devices.

Following peripheral devices and interface cables were connected during the measurement:

Device	Manufacture	Model	Description
VGA & Stereo Audio/Digital CAT5 Extender and Distributor *	SMART CABLING & TRANSMISSION CORP.	VEXXDALX	1.48m Non-Shielded AC Adapter power cord 3.0m Non-Shielded RJ-45 cable *2 1.84m Non-Shielded earphone cable *2 1.83m Shielded VGA cable with 2 core*2 1.48m S Non-Shielded optical cable 1.45 m Shielded AV cable
PC	Lenovo	7298 RN1	1.8m Unshielded AC Adaptor Power Cord
LCD TV	SONY	KDL-20S4000	1.6m Unshielded AC Power Cord
Keyboard	Logitech	M-U0026	1.5m Unshielded Cable
Mouse	Logitech	M-BE58	1.5m Unshielded Cable

Remark “*” means equipment under test.

2.4 Deviation Record

No deviations were required.

2.5 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Uncertainty
Conducted emissions	150kHz ~ 30MHz	2.45(Mains)
Conducted emission at telecommunication ports	150kHz ~ 30MHz	2.22(Voltage)
		2.88(Current)
Radiated emissions	30MHz ~ 1GHz	3.90($30\text{MHz} \leq f \leq 300\text{MHz}$)
		3.95($300\text{MHz} < f \leq 1\text{GHz}$)
	Above 1GHz	4.42($1\text{GHz} \leq f \leq 18\text{GHz}$)

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

2.6 Description of Test Mode

The EUT is designed with AC power supply of 100-240Vac, 50-60Hz or radiated emission evaluation, 230Vac/50Hz had been covered during the pre-test. The worst radiated emission data was found at 230Vac/50Hz and recorded in the applied test report.

The EUT has been pre-tested under following modes, and mode 1 is the worst case for final emission test.

Test Mode	Test condition
1	Operation Mode: VGA 1600 x 1200@85Hz

2.7 Modification Record

No modifications were required. (That is the EUT complied with the requirement as tested.)

3 SUMMARY OF TEST RESULTS

3.1 Emissions

3.1.1 Conducted Emissions

[X] – PASS (VGA 1600 x 1200@85Hz -Neutral)

Minimum EMI Margin to the limit: -8.95 dB at 3.1730 MHz

[X] – PASS (VGA 1600 x 1200@85Hz -Line)

Minimum EMI Margin to the limit: -2.20 dB at 3.0740 MHz

3.1.2 Conducted Telecommunication ports

Not Applicable

3.1.3 Radiated Emissions

[X] – PASS (VGA 1600 x 1200@85Hz -HOR)

Minimum EMI Margin to the limit: -6.80 dB at 176.6100 MHz

[X] – PASS (VGA 1600 x 1200@85Hz -VER)

Minimum EMI Margin to the limit: -3.30 dB at 43.5000 MHz

3.1.4 Harmonics Current Emissions

[X] -PASS

The harmonics current values were under the limits of the class A equipment of the EN 61000-3-2.

3.1.5 Voltage Fluctuations and Flicker

[X] -PASS

The voltage fluctuations and flicker values were under the limits of the EN 61000-3-3 requirements.

3.2 Immunity

3.2.1 Immunity Criteria

The results of all of the immunity tests performed on the EUT were evaluated according to the following criteria, and according to the manufacturer's specifications for the EUT:

Performance criterion A : The EUT continued to operate as intended. No degradation of performance or loss of function was allowed below a performance level specified by the manufacturer, when the EUT was used as intended.

Performance criterion B : The EUT continued to operate as intended after the test. No degradation of performance or loss of function was allowed below a performance level specified by the manufacturer, when the EUT was used as intended. During the test, degradation of performance was however allowed. No change of actual operating state or stored data was allowed.

Performance criterion C : Temporary loss of function was allowed, provided the function was self recoverable or could be restored by the operation of the controls.

3.2.2 Electrostatic Discharge Immunity

- No Degradation of Function

- Distortion of Function

- Error of Function

Requirement :Criterion B (or better)

- Satisfies Criterion A

- Satisfies Criterion B

- Satisfies Criterion C

3.2.3 RF Radiated Fields Immunity

- No Degradation of Function

- Distortion of Function

- Error of Function

Requirement :Criterion A

- Satisfies Criterion A

- Satisfies Criterion B

- Satisfies Criterion C

3.2.4 EFT/Burst Immunity

Requirement :Criterion B(or better)

- | | |
|--|-------------------------|
| <input checked="" type="checkbox"/> - No Degradation of Function | - Satisfies Criterion A |
| <input type="checkbox"/> - Distortion of Function | - Satisfies Criterion B |
| <input type="checkbox"/> - Error of Function | - Satisfies Criterion C |

3.2.5 Surge Immunity

Requirement :Criterion B (or better)

- | | |
|--|-------------------------|
| <input checked="" type="checkbox"/> - No Degradation of Function | - Satisfies Criterion A |
| <input type="checkbox"/> - Distortion of Function | - Satisfies Criterion B |
| <input type="checkbox"/> - Error of Function | - Satisfies Criterion C |

3.2.6 RF Common Mode Immunity

Requirement :Criterion A

- | | |
|--|-------------------------|
| <input checked="" type="checkbox"/> - No Degradation of Function | - Satisfies Criterion A |
| <input type="checkbox"/> - Distortion of Function | - Satisfies Criterion B |
| <input type="checkbox"/> - Error of Function | - Satisfies Criterion C |

3.2.7 Power Frequency Magnetic Field Immunity

Requirement :Criterion A

- | | |
|--|-------------------------|
| <input checked="" type="checkbox"/> - No Degradation of Function | - Satisfies Criterion A |
| <input type="checkbox"/> - Distortion of Function | - Satisfies Criterion B |
| <input type="checkbox"/> - Error of Function | - Satisfies Criterion C |

3.2.8 Voltage Interruptions and Voltage Dips Immunity

Requirement :Criterion C (or better)

- | | |
|--|-------------------------|
| <input type="checkbox"/> - No Degradation of Function | - Satisfies Criterion A |
| <input checked="" type="checkbox"/> - Distortion of Function | - Satisfies Criterion B |
| <input type="checkbox"/> - Error of Function | - Satisfies Criterion C |

4 TEST DATA & RELATED INFORMATIONS

4.1 Emissions

4.1.1 Conducted Emissions Test

4.1.1.1 Limit of Conducted Emission Measurement

Frequency (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15-0.5	79	66	66-56	56-46
0.5-5	73	60	56	46
5-30	73	60	60	50

NOTE: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.1.1.2 Test Instruments

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
EMI Test Receiver	Rohde & Schwarz	ESCI	2011/02/03	2012/02/02
LISN	EMCO	3625/2	2011/03/01	2012/02/28
LISN	Rohde & Schwarz	ESH2-Z5	2010/08/10	2011/08/09
Current Probe	Rohde & Schwarz	ESH2-Z1	2010/10/27	2011/10/26
ISN	FCC	FCC-TLISN-T2-02	2010/10/08	2011/10/07
ISN	RCC	FCC-TLISN-T4-02	2010/10/08	2011/10/07
ISN	RCC	FCC-TLISN-T8-02	2010/10/08	2011/10/07
EMI Test Receiver	Rohde & Schwarz	ESCI	2011/02/03	2012/02/02


4.1.1.3 Conducted Emissions Test Data

Operating Conditions of The EUT : VGA 1600 x 1200@85Hz

Test Date : Jun.21, 2011

Test Specification	EN 55022:2006/A1:2007 (Class B)	
Climatic Condition	Ambient Temperature: <u>26</u> °C	Relative Humidity: <u>55</u> %RH
Power Supply System	AC Power : <u>230</u> Vac <u>50</u> Hz	
Test Set-up	Table-top Equipment	

Test data see the next pages.




Site	: conducted #1	Date	: 06-21-2011
Condition	: CLASS-B QP	LISN	: NEUTRAL
Tem / Hum	: 26 °C / 55%	Test Mode	: VGA 1600 x 1200@85Hz
EUT	: 11-02-RBF-094	Power Rating	: 230Vac/50Hz
Memo	:	Memo	:

Freq (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBuV)	Limit Line (dBuV)	Over Limit (dB)	Remark
0.1524	33.36	0.50	33.86	55.87	-22.01	Average
0.1524	50.66	0.50	51.16	65.87	-14.71	QP
0.1955	30.10	0.50	30.60	53.80	-23.20	Average
0.1955	46.73	0.50	47.23	63.80	-16.57	QP
0.9582	27.82	0.54	28.36	46.00	-17.64	Average
0.9582	36.31	0.54	36.85	56.00	-19.15	QP
3.1730	36.39	0.66	37.05	46.00	-8.95	Average
3.1730	46.16	0.66	46.82	56.00	-9.18	QP
3.7590	28.99	0.69	29.68	46.00	-16.32	Average
3.7590	37.55	0.69	38.24	56.00	-17.76	QP
9.2040	37.01	0.84	37.85	50.00	-12.15	Average
9.2040	47.37	0.84	48.21	60.00	-11.79	QP

Note :

1. Result = Reading + Factor
2. Factor = LISN Factor + Cable Loss



Site	: conducted #1	Date	: 06-21-2011
Condition	: CLASS-B QP	LISN	: LINE
Tem / Hum	: 26 °C / 55%	Test Mode	: VGA 1600 x 1200@85Hz
EUT	: 11-02-RBF-094	Power Rating	: 230Vac/50Hz
Memo	:	Memo	:

Freq (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBuV)	Limit Line (dBuV)	Over Limit (dB)	Remark
0.1540	39.62	0.49	40.11	55.78	-15.67	Average
0.1540	51.40	0.49	51.89	65.78	-13.89	QP
0.1815	29.41	0.50	29.91	54.42	-24.51	Average
0.1815	47.44	0.50	47.94	64.42	-16.48	QP
1.5350	37.79	0.57	38.36	46.00	-7.64	Average
1.5350	36.45	0.57	37.02	56.00	-18.98	QP
3.0740	42.06	0.66	42.72	46.00	-3.28	Average
3.0740	53.14	0.66	53.80	56.00	-2.20	QP
4.6220	42.43	0.72	43.15	46.00	-2.85	Average
4.6220	51.80	0.72	52.52	56.00	-3.48	QP
6.1530	33.40	0.76	34.16	50.00	-15.84	Average
6.1530	41.76	0.76	42.52	60.00	-17.48	QP
7.7280	41.60	0.82	42.42	50.00	-7.58	Average
7.7280	50.58	0.82	51.40	60.00	-8.60	QP
9.2040	42.37	0.84	43.21	50.00	-6.79	Average
9.2040	50.98	0.84	51.82	60.00	-8.18	QP
15.3880	38.85	1.01	39.86	50.00	-10.14	Average
15.3880	47.48	1.01	48.49	60.00	-11.51	QP

Note :

1. Result = Reading + Factor
2. Factor = LISN Factor + Cable Loss

4.1.1.4 Conducted Emissions Test Setup Photos



4.1.2 Conducted Telecommunication ports Test

4.1.2.1 Conducted Telecommunication ports Test Data

Not Applicable

4.1.3 Radiated Emissions Test

4.1.3.1 Limit of Radiated Emission Measurement.

Frequency (MHz)	Class A (at 10m)	Class B (at 10m)
	Quasi-peak (dBuV/m)	Quasi-peak (dBuV/m)
30-230	40	30
230-1000	47	37

Frequency (MHz)	Class A (at 3m)		Class B (at 3m)	
	Peak (dBuV/m)	Average (dBuV/m)	Peak (dBuV/m)	Average (dBuV/m)
1000-3000	76	56	70	50
3000-6000	80	60	74	54

NOTE: 1. The lower limit shall apply at the transition frequencies.

2. Emission level (dBuV/m) = 20 log Emission level (uV/m).

Frequency range of radiated measurement

Highest frequency generated or used within the EUT or on which the WUT operates or tunes (MHz)	Upper frequency of measurement rang (MHz)
Below 108	1000
108-500	2000
500-1000	5000
Above 1000	Up to 5 times of the highest frequency to 6 GHz, whichever is less

4.1.3.2 Test Instruments

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Test Receiver	Rohde & Schwarz	ESVS30	2011/05/13	2012/05/12
Amplifier	HP	8447D	2011/05/09	2012/05/08
Spectrum	Advantest	R3162	2011/03/03	2012/03/01
Bi-Log Antenna	Schaffner	CBL 6111	2011/05/20	2012/05/19
Test Receiver	Rohde & Schwarz	ESU40	2010/08/05	2011/08/04
Amplifier	HP	8449B	2010/12/29	2011/12/28
Horn Antenna	EMCO	3115	2011/05/10	2012/05/09

4.1.3.3 Radiated Emissions Test Data


Operating Conditions of The EUT : VGA 1600 x 1200@85Hz

Test Date : Jun. 20, 2011

Test Specification	EN 55022:2006/A1:2007 (Class B)
Climatic Condition	Ambient Temperature: <u>30</u> °C Relative Humidity: <u>58</u> %RH
Power Supply System	AC Power : <u>230</u> Vac <u>50</u> Hz
Test Set-up	Table-top Equipment

Test data see the next pages.

(30MHz to 1GHz)




Site	:Open site #2	Date	:2011-06-20
EUT	:11-02-RBF-094	Ant. Pol.	:HORIZONTAL
Model	:Operation	Detector	:QP
Power Rating		:230Vac/50Hz	Engineer :
Limit	:CLASS-B	Temp.	:30 °C
Memo	: VGA 1600 x 1200@85Hz	Humi.	:58 %

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB
34.0500	1.11	17.79	18.90	30.00	-11.10
106.1400	4.60	12.80	17.40	30.00	-12.60
176.6100	11.18	12.02	23.20	30.00	-6.80
232.5000	6.97	14.13	21.10	37.00	-15.90
480.6000	-5.43	22.53	17.10	37.00	-19.90
775.3000	-7.66	28.86	21.20	37.00	-15.80

Note :

1. Result = Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
3. The expanded uncertainty of the radiated emission tests is 3.53 dB.
4. The margin value=Limit – Result



Site	:Open site #2	Date	:2011-06-20
EUT	:11-02-RBF-094	Ant. Pol.	:VERTICAL
Model	:Operation	Detector	:QP
Power Rating		:230Vac/50Hz	Engineer :
Limit	:CLASS-B	Temp.	:30 °C
Memo	: VGA 1600 x 1200@85Hz	Humi.	:58 %

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB
35.4000	7.29	16.71	24.00	30.00	-6.00
43.5000	14.59	12.11	26.70	30.00	-3.30
105.3300	8.30	12.80	21.10	30.00	-8.90
169.0500	7.74	12.46	20.20	30.00	-9.80
498.1000	-6.26	22.96	16.70	37.00	-20.30
716.5000	-7.29	27.49	20.20	37.00	-16.80

Note :

1. Result = Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
3. The expanded uncertainty of the radiated emission tests is 3.53 dB.
4. The margin value=Limit - Result



(Above 1GHz)

Not Applicable

4.1.3.4 Radiated Emissions Test Setup Photos

(30MHz to 1GHz)



4.1.4 Harmonics Current Emissions Test

4.1.4.1 Test Instruments

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Harmonics-1000	EMC-Partner	Harmonics-1000	2010/12/17	2011/12/16

4.1.4.2 Harmonics Current Emissions Test Data

Operating Conditions of The EUT : Operation

Test Date : Jun. 21, 2011

Test Specification	EN 61000-3-2:2006/A1:2009/A2:2009		
Climatic Condition	Ambient Temperature: <u>28</u> °C	Relative Humidity: <u>49</u> %RH	
Power Supply System	AC Power : <u>230</u> Vac <u>50</u> Hz		
Test Set-up	Table-top Equipment		

Test data see the next pages.

Operator : Urms = 229.9V Freq = 49.987 Range: 0.5 A
 Unit : Irms = 0.058A Ipk = 0.273A cf = 4.746
 Serialnumber : P = 5.780W S = 13.25VA pf = 0.436
 Remarks : THDi = 90.70% THDu = 0.10% Class A

Test - Time : 3min -100%

Test completed, Result: PASSED

Order	Freq. [Hz]	Iavg [A]	I _{max} [A]	Limit [A]	Order	Freq. [Hz]	Iavg [A]	I _{max} [A]	Limit
1	50	0.0251	0.0253		21	1050	0.0076	0.0076	0.1071
2	100	0	0.0006	1.08	22	1100	0	0.0006	0.0836
3	150	0.0226	0.0226	2.3	23	1150	0.006	0.006	0.0978
4	200	0	0.0006	0.43	24	1200	0	0.0006	0.0767
5	250	0.0219	0.0219	1.14	25	1250	0	0.0047	0.09
6	300	0	0.0006	0.3	26	1300	0	0.0006	0.0708
7	350	0.0208	0.0208	0.77	27	1350	0	0.0038	0.0833
8	400	0	0.0006	0.23	28	1400	0	0.0005	0.0657
9	450	0.0193	0.0193	0.4	29	1450	0	0.0032	0.0776
10	500	0	0.0007	0.184	30	1500	0	0.0005	0.0613
11	550	0.0176	0.0176	0.33	31	1550	0	0.0031	0.0726
12	600	0	0.0007	0.1533	32	1600	0	0.0005	0.0575
13	650	0.0156	0.0157	0.21	33	1650	0	0.003	0.0682
14	700	0	0.0007	0.1314	34	1700	0	0.0005	0.0541
15	750	0.0136	0.0136	0.15	35	1750	0	0.003	0.0643
16	800	0	0.0006	0.115	36	1800	0	0.0005	0.0511
17	850	0.0115	0.0115	0.1324	37	1850	0	0.0029	0.0608
18	900	0	0.0006	0.1022	38	1900	0	0.0005	0.0484
19	950	0.0095	0.0095	0.1184	39	1950	0	0.0027	0.0577
20	1000	0	0.0006	0.092	40	2000	0	0.0005	0.046

4.1.4.3 Harmonics Current Emissions Test Setup Photos



4.1.5 Voltage Fluctuations and Flicker Test

4.1.5.1 Test Instruments

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Harmonics-1000	EMC-Partner	Harmonics-1000	2010/12/17	2011/12/16

4.1.5.2 Voltage Fluctuations and Flicker Test Data

Operating Conditions of The EUT : Operation

Test Date : Jun. 24, 2011

Test Specification	EN 61000-3-3:2008		
Climatic Condition	Ambient Temperature: <u>28</u> °C	Relative Humidity: <u>49</u> %RH	
Power Supply System	AC Power : <u>230</u> Vac <u>50</u> Hz		
Test Set-up	Table-top Equipment		

	Test Data	Limit	Pass or Fail
Plt	0.072	0.65	Pass
Pst	0.072	1.00	Pass
dt	0.00 ms	500 ms	Pass
dmax	0.00 %	4.0 %	Pass
dc	0.00 %	3.3 %	Pass

4.1.5.2 Voltage Fluctuations and Flicker Test Setup Photos



4.2 Immunity

4.2.1 Electrostatic Discharge Immunity Test

4.2.1.1 Test Instruments

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Electrostatic Discharge Simulator	Noiseken	ESS2002	2010/10/08	2011/10/07

4.2.1.2 Electrostatic Discharge Immunity Test Data

Test data see the next pages.

Operating Conditions of The EUT : Operation

Test Date : Jun. 24, 2011

Test Specification	IEC 61000-4-2:2008
Climatic Condition	Ambient Temperature: <u>28</u> °C Relative Humidity: <u>48</u> %RH
	Atmospheric Pressure : 990 mbar
Power Supply System	AC Power : <u>230</u> Vac <u>50</u> Hz
Test Set-up	Table-top Equipment

Energy-Storage Capacitor : <u>150</u> pF	Contact Discharge Times : <u>25</u> times/each condition															
Discharge Resistor : <u>330</u> Ω	Air Discharge Times : <u>10</u> times/each condition															
\ Discharge Mode	Contact Discharge								Air Discharge							
\ESD Voltage	<u>2</u> kV		<u>4</u> kV		___ kV		___ kV		<u>2</u> kV		<u>4</u> kV		<u>8</u> kV		___ kV	
\Points\Result\Polarity	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-
VCP	A	A	A	A	---	---	---	---	---	---	---	---	---	---	---	---
HCP	A	A	A	A	---	---	---	---	---	---	---	---	---	---	---	---
P1-P2,P8-P10	A	A	A	A	---	---	---	---	---	---	---	---	---	---	---	---
P3-P7	---	---	---	---	---	---	---	---	A	A	A	A	A	A	---	---

Note : “---“means the test could not be carrier out.

“ A ” means the EUT’s function was correct normal performance during the test.

TEST POINTS



TEST POINTS



4.2.1.3 Electrostatic Discharge Immunity Test Setup Photos



4.2.2 RF Radiated Fields Immunity Test

4.2.2.1 Test Instruments

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Antenna	AR	AT5080	N/A	N/A
signal Generator	Aglient	E4421B	2010/08/03	2011/08/02
Amplifier	Ophir	5172	N/A	N/A
Amplifier	Ophir	5127	N/A	N/A
POWER METER	Boonton	4232A	2010/08/06	2011/08/05


4.2.2.2 RF Radiated Fields Immunity Test Data

Test data see the next pages.

Operating Conditions of The EUT : Operation

Test Date : Jun. 23, 2011

Test Specification	IEC 61000-4-3:2006/A1:2007/A2:2010
Climatic Condition	Ambient Temperature: <u>28</u> °C Relative Humidity: <u>55</u> %RH
	Atmospheric Pressure : 990 mbar
Power Supply System	AC Power : <u>230</u> Vac <u>50</u> Hz
Test Set-up	Table-top Equipment



Frequency Range: <u>80</u> MHz ~ <u>1000</u> MHz		Field Strength: <u>3</u> V/m	Modulation (AM 1KHz 80%)
Sweep Rate : $\leq 1.5 \times 10^{-3}$ decades/s	Step Size : ≤ 1 % of preceding frequency value	Dwell time : 2.9 s	
Frequency Range (MHz)	Antenna-Polarization	Direction of Device	Test Result
80~1000	Horizontal	front	A
		rear	A
		left	A
		right	A
80~1000	Vertical	front	A
		rear	A
		left	A
		right	A

Note : “A” means the EUT’s function was correct normal performance during the test.

4.2.2.3 RF Radiated Fields Immunity Test Setup Photos



4.2.3 EFT/Burst Immunity Test

4.2.3.1 Test Instruments

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
EMC Immunity Tester	EMC-PARTNER	TRANSIENT-1000	2010/08/17	2011/08/16

4.2.3.2 EFT/Burst Immunity Test Data

Test data see the next pages.

Operating Conditions of The EUT : Operation



Test Date : Jun. 22, 2011

Test Specification	IEC 61000-4-4:2004/A1:2010
Climatic Condition	Ambient Temperature: <u>28</u> °C Relative Humidity: <u>49</u> %RH
	Atmospheric Pressure : 990 mbar
Power Supply System	AC Power: <u>230</u> Vac <u>50</u> Hz
Test Set-up	Table-top Equipment

Pulse : 5 /50ns Burst : 15ms /300ms		Repetition Rate : <u>5kHz</u>		Test time : <u>1</u> min/each condition	
\Voltage\Polarity\ \Test Point\Mode\Result\		<u>1.0 kV</u>			
		+	-		
Power Line	L	A	A		
	N	A	A		
	L-N	A	A		
\Voltage\Polarity\ \Test Point\Mode\Result\		<u>0.5 kV</u>			
		+	-		
RJ-45 cable(In)		A	A		
RJ-45 cable(Out)		A	A		

Note : “A” means the EUT’s function was correct normal performance during the test.

4.2.3.3 EFT/Burst Immunity Test Setup Photos



4.2.4 Surge Immunity Test

4.2.4.1 Test Instruments

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
EMC Immunity Tester	EMC-PARTNER	TRANSIENT-1000	2010/08/17	2011/08/16

4.2.4.2 Surge Immunity Test Data

Test data see the next pages.

Operating Conditions of The EUT : Operation

Test Date : Jun. 24, 2011

Test Specification	IEC 61000-4-5:2005
Climatic Condition	Ambient Temperature: <u>28</u> °C Relative Humidity: <u>49</u> %RH
	Atmospheric Pressure : <u>990</u> mbar
Power Supply System	AC Power: <u>230</u> Vac <u>50</u> Hz
Test Set-up	Table-top Equipment

Waveform : 1.2/50µs(8/20µs)		Repetition rate : <u>60</u> sec		Times : <u>5</u> time/each condition		
\Phase \Voltage \Mode \Polarity \Result			0°	90°	180°	270°
0.5kV	L – N	+	A	A	A	A
		–	A	A	A	A
1.0kV	L – N	+	A	A	A	A
		–	A	A	A	A

Note : “A” means the EUT’s function was correct normal performance during the test.

4.2.4.3 Surge Immunity Test Setup Photos



4.2.5 RF Common Mode Immunity Test

4.2.5.1 Test Instruments

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
CS TESTER	FRANKONIA	CIT-10	2010/11/17	2011/11/16
M2+3 CDN-KIT	FRANKONIA	M2+3	2010/10/08	2011/10/07
SCHAFFUER	CS-CLAMP	KEMZ801	2010/11/17	2011/11/16

4.2.5.2 RF Common Mode Immunity Test Data

Test data see the next pages.

Operating Conditions of The EUT : Operation


Test Date : Jun. 23, 2011

Test Specification	IEC 61000-4-6:2008
Climatic Condition	Ambient Temperature: <u>28</u> °C Relative Humidity: <u>55</u> %RH
Power Supply System	AC Power : <u>230</u> Vac <u>50</u> Hz
Test Set-up	Table-top Equipment

Frequency Range	: 0.15 MHz ~ 80 MHz	Test Level	: <u>3</u> Vrms	Modulation (AM 1kHz 80%)
Sweep Rate	: $\leq 1.5 \times 10^{-3}$ decades/s	Step Size	: ≤ 1 % of preceding frequency value	
				Dwell Time : <u>2.9</u> s
Frequency Range (MHz)	Tested Line		Test Result	
0.15~80	M2		A	
0.15~80	RJ-45 cable(In) (clamp)		A	
0.15~80	RJ-45 cable(Out) (clamp)		A	

Note : “A” means the EUT’s function was correct normal performance during the test.

4.2.5.3 RF Common Mode Immunity Test Setup Photos



4.2.6 Power Frequency Magnetic Field Immunity Test

4.2.6.1 Test Instruments

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
EMC Immunity Tester	EMC-PARTNER	TRANSIENT-1000	2010/08/17	2011/08/16
Mfgenerator	EMC-PAPTNER	MF-1000	2011/03/09	2012/03/08




4.2.6.2 Power Frequency Magnetic Field Immunity Test Data

Test data see the next pages.

1 Operating Conditions of The EUT : Operation

Test Date : Jun. 22, 2011


Test Specification	IEC61000-4-8:2009	
Climatic Condition	Ambient Temperature: <u>28</u> °C	Relative Humidity: <u>49</u> %RH
	Atmospheric Pressure : <u>990</u> mbar	
Power Supply System	AC Power : <u>230</u> Vac <u>50</u> Hz	
Test Set-up	Table-top Equipment	



Magnetic field frequency : <u>50</u> Hz		Continuous magnetic field strength : <u>1</u> A/m	
Magnetic field direction		Testing result	
X - Axis		A	
Y - Axis		A	
Z - Axis		A	

Note : “A” means the EUT’s function was correct normal performance during the test.

4.2.6.3 Power Frequency Magnetic Field Immunity Test Setup Photos



4.2.7 Voltage Interruptions and Voltage Dips Immunity Test

4.2.7.1 Test Instruments

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
EMC Immunity Tester	EMC-PARTNER	TRANSIENT-1000	2010/08/17	2011/08/16

4.2.7.2 Voltage Interruptions and Voltage Dips Immunity Test Data

Test data see the next pages.

Operating Conditions of The EUT : Operation

Test Date : Jun. 22, 2011

Test Specification	IEC 61000-4-11:2004
Climatic Condition	Ambient Temperature: <u>28</u> °C Relative Humidity: <u>49</u> %RH
Power Supply System	AC Power: <u>100</u> Vac <u>60</u> Hz; AC Power: <u>240</u> Vac <u>50</u> Hz
Test Set-up	Table-top Equipment

Test mode	Voltage dips	Durations (periods)	Interval(s)	Times	Phase	Result
Voltage interruptions	>95%	250	10	3	0°/180°	B
	>95%	300	10	3	0°/180°	B
Voltage dips in %U _T	>95%	0.5	10	3	0°/180°	B
	30%	25	10	3	0°/180°	A
	30%	30	10	3	0°/180°	A

Note : “A” means the EUT’s function was correct normal performance during the test.

“B” means the EUT’s function was temporary loss of function or degradation of performance during the test. After test, the EUT recovers its normal performance, without operator intervention.

4.2.7.3 Voltage Interruptions and Voltage Dips Immunity Test Setup Photos



CONSTRUCTED PHOTOS of EUT

A)EUT

1. Front View of EUT



2. Side View of EUT



CONSTRUCTED PHOTOS of EUT

3. Side View of EUT




4. Rear View of EUT




CONSTRUCTED PHOTOS of EUT

5. Internal View of EUT




CONSTRUCTED PHOTOS of EUT

6. Component View of PCB




7. Component View of PCB



CONSTRUCTED PHOTOS of EUT

8. Solder View of PCB



CONSTRUCTED PHOTOS of EUT

B)Adapter

1. Total View of Adapter



2. Front View of EUT



CONSTRUCTED PHOTOS of EUT

3. Side View of EUT



4. Side View of EUT



CONSTRUCTED PHOTOS of EUT

5. Rear View of EUT

