

Component Video Distribution Amplifier Series

ITEM NO.: YD02A, YD02D, YD04A, YD04D



YD02A, YD02D, YD02D, YD04D are component video with analog stereo/digital audio distribution amplifiers for AV signals. They can accept a component signal input from a DVD, projector and the output is amplified to allow connection of multi display monitors. All of them could be stackable for large displays.

YD02A 1 Input 2 Output Component Video Distribution Amplifier with Stereo Audio

- 1 x Input: component video and left, right audio.
- 2 x Output: component video and left, right audio.
- Support 480i, 480p, 576i, 576p, 720p, 1080i, 1080p.
- Video Bandwidth up to 400Mhz.
- Cascade connection several units for larger displays with great picture quality.

YD02D 1 Input 2 Output Component Video Distribution Amplifier with Digital/Optical audio

- Identical to YD02A, but digital audio instead of stereo audio.
- Digital Audio: Coax or Optical option.

YD04A 1 Input 4 Output Component Video Distribution Amplifier with Stereo Audio


- 1 x Input: Component video and left, right audio.
- 4 x Output: Component video and left, right audio.
- Support 480i, 480p, 576i, 576p, 720p, 1080i, 1080p.
- Video Bandwidth up to 400Mhz.
- Cascade connection several units for larger displays with great picture quality.

YD04D 1 Input 4 Output Component Video Distribution Amplifier with Digital/Optical audio

- Identical to CD04A, but digital audio instead of stereo audio.
- Digital Audio: Coax or Optical option.

Installation View:


YD02A




YD02D



YD04A



YD04D



Specification:

ITEM NO.	YD02A	YD02D	YD04A	YD04D
Input Resolution	480i, 480p, 576i, 576p, 720p, 1080i, 1080p.			
Video Bandwidth	400Mhz			
Video Input	RCA x 3 : Y (75Ω , 1.0 Vp-p) , Pb Pr (75Ω , 0.7 Vp-p)			
Video Output	RCA x 6		RCA x 12	
Audio Bandwidth	DC-20Khz			
Audio Input	RCA x 2 (10KΩ)	X	RCA x 2 (10KΩ)	X
Audio Output	RCA x 4 (10KΩ)	X	RCA x 8 (10KΩ)	X
Digital Audio Input	X	Coaxial RCA x 1 (75Ω) , Optical x 1	X	Coaxial RCA x 1 (75Ω) , Optical x 1
Digital Audio Output	X	Coaxial RCA x 2 (75Ω) , Optical x 2	X	Coaxial RCA x 4 (75Ω) , Optical x 4
Power Supply	DC 5V 500mA			
Power Consumption	300mA (Max)			
Temperature	Operation: 0 to 55°C, Storage: -20 TO 85°C, Humidity: up to 95%			
Dimensions mm	145 x 97 x 37		225 x 167 x 40	
Weight g	305	315	800	825

RoHS CE FC

Rev. B