

# TWISTED PAIR TRANSMISSION SYSTEM – Passive Series

**ITEM NO.: TTP111HDLK (TTP111HD , TTP111HDL)  
HD Video Transceiver (BALUN)**



### TTP111HD

- To send HD-CVI, HD-TVI, AHD signal 720p at 300M, 1080p at 200M over UTP cable.
- BNC male to screw terminal for easy connection.
- Compact and mini size, could mount multiple units behind multiplexer, Quad, DVR..etc
- Passive, no power required.
- Eliminate coaxial cable.
- To work with Active transmitter TTA111HDT, Active receiver TTA111HDR for extra long distance transmission.

### TTP111HDL


- Identical to the TTP111H, but BNC male to screw terminal with 10cm mini coax cable for easy connection.
- Compact and mini size, could mount multiple units behind multiplexer, Quad, DVR..etc.

### Panel View:

#### TTP111HD



#### TTP111HDL



### Installation View



This installation should be made by a qualified service person and should conform to all local codes.

### Specification:

ITEM NO.	TTP111HD	TTP111HDL
Video Input / Output Terminals	BNC MALE (75Ω · 1V p-p)	
Video Onput / Iutput Terminals	TERMINAL BLOCK	
Bandwidth	50Hz ~ 47MHz (-3dB)	
Transmission Distance	720p 300M, 1080p 200M (Max)	
Temperature	Operation: 0 to 55°C, Storage: -20 TO 85°C, Humidity: up to 95%	
Dimension mm	14.5 × 49.5 × 15.5	14.5 × 15.5 × 145, include 100mm mini coax cable
Weight	18	25



Rev. A